

LIGHTS	MOLEX CONNECTOR	AMPHENOL MALE (Pigtail)	METAL CONNECTOR	APPLICATIONS	DESCRIPTION	MAXIMUM DC CURRENT CONSUMPTION AT 12V AND T _a = 25°C (mA)
	CX300-001	CX302-001	CX301-001	Ambient	IS Light, Ambient, 6xWhite 60 Deg	655
	CX300-002	CX302-002	CX301-002	Driving	IS Light, Driving, 6xWhite, 4x5 Deg, 2x60 Deg	655
	CX300-003	CX302-003	CX301-003	Spot Light	IS Light, Driving Spot, 6xWhite 5 Deg	655
	CX300-004	CX302-004	CX301-004	Reverse Tail	IS Light, Reverse/Ambient+Tail, 4xWhite, 2xRed, 6x60 Deg	457
	CX200-006	CX302-006	-	Remote/Injury	IS Light, Remote/Injury, Blue Antiphase Flashing (630mHz), 2xDNP, 4x60 Deg	390
	CX200-007	CX302-007	CX201-007	Hazard	IS Light, Hazard, Yellow Antiphase Flashing (630mHz), 2xDNP, 4x60 Deg	298
	CX300-009	CX302-009	-	TAIL +Spotlight	IS Light, 4xWhite 5 Deg, 2xRed 60 Deg	457
	CX300-009-MAX	CX302-009-MAX	-	TAIL +Spotlight	IS Light, 4xWhite 5 Deg, 2xRed 60 Deg, White Maximum Brightness (50% more than CX30X-009)	1216
	CX200-011	CX302-011	-	Traffic	IS Light, 2xRed, 2xYellow, 2xGreen, 6x60 Deg, Green 10% Brightness	142
	CX300-013	CX302-013	-	Area Light	IS Light, Ambient, 6xWhite 60 Deg (Half Brightness), V _{min} = 6.5V	309
		CX302-013-TW			IS Light, Ambient, 6xWhite 60 Deg (Half Brightness), Two-Wire, V _{min} = 6.5V	
	CX300-014	CX302-014	-	Ambient Hazard	IS Light, Ambient, 4xWhite, 2xYellow Flashing (630mHz), 6x60 Deg	586
	-	CX302-015	-	BSL	IS Light, BSL, 4xRed, 2xWhite, 6x60 Deg	1022
	CX200-017	CX302-017	-	Mode	IS Light, Mode Lights, 2xRed, 2xYellow, 2xGreen, 6x60 Deg, Maximum Brightness	799
	CX200-019	CX302-019	-	Solid Green	IS Light, Solid Green, 6xGreen 60 Deg	445
	CX200-020	CX302-020	CX201-020	EmergencyHazard	IS Light, EmergencyHazard, Red Antiphase Flashing (630mHz), 2xDNP, 4x60 Deg, 100% Brightness	643
	-	CX302-021	-	Flashing Green	IS Light, Flashing Green (750mHz), 6xGreen 60 Deg	176
	-	CX302-022	-	Green Red Status	IS Light, 4xGreen, 2xRed, 6x60 Deg, Maximum Brightness	651
	-	CX302-023	-	Hazard/Solid Red	IS Light, 6xRed 60 Deg, Maximum Brightness	993
	CX200-028	CX302-028	-	EmergencyHazard	IS Light, Yellow, 2xDNP, 4x60 Deg, 4mA per Bank	8
	-	CX302-029	-	Cut-through/Awareness	IS Light, 4xWhite, 2xGreen, 6x60 Deg	558
	-	CX302-030	-	Ambient Hazard	IS Light, Ambient, 4xWhite 5 Deg, 2xYellow Flashing (630mHz) 60 Deg, White High Brightness	1118
	CX300-050	CX302-050	-	Ambient	IS Light, Ambient, 6xWhite 60 Deg, 80% Brightness	525
	-	CX302-051	-	Ambient	IS Light, Ambient, 6xWhite 60 Deg, 65% Brightness, V _{min} = 8.5V	422
	CX300-052	-	-	Green Signal Light	IS Light, Green, 2xDNP, 4x60 Deg, 4mA per Bank	8
	CX300-053	-	-	Ambient	IS Light, White, 4x60 Deg, 90% Brightness, 2x60 Deg, 10% Brightness	405
		CX302-101				
	CX300-101	CX302-101	CX301-101	Ambient	IS Light, Ambient, 6xWhite 60 Deg, 90% Brightness	580
		CX302-101-TW			IS Light, Ambient, 6xWhite 60 Deg, 90% Brightness, Two-Wire	



AMPHENOL PIGTAIL



MOLEX CONNECTOR



METAL CONNECTOR

